

SECONDARY BATTERY SEPARATOR, ITS MANUFACTURE AND ALKALINE SECONDARY BATTERY USING THIS SEPARATOR

SECONDARY BATTERY SEPARATOR, ITS MANUFACTURE AND ALKALINE SECONDARY BATTERY USING THIS SEPARATOR

Patent Number: JP8185847
Publication date: 1996-07-16
Inventor(s): OBATA TSUTOMU; NISHIDA MASAOKI
Applicant(s):: KANAI HIROAKI
Requested Patent: ☐ JP8185847
Application Number: JP19940327064 19941228
Priority Number(s):
IPC Classification: H01M2/16 ; H01M10/24
EC Classification:
EC Classification:
Equivalents: JP2726633B2

Abstract

PURPOSE: To provide a secondary battery separator with low self-discharge capability and high hydrophilic nature by covering a polyolefin resin porous body with a partially crosslinked polymer of a reactive surfactant and a vinyl resin monomer by chemical bond.

CONSTITUTION: A solution containing a reactive surfactant and a vinyl resin monomer or oligomer is applied to a film or nonwoven fabric porous body made of polyolefin resin containing 0.1% or less each antioxidant and ultraviolet absorber, then they are heat-treated. The reactive surfactant preferably has polyethylene oxide in the structure. The vinyl resin monomer preferably contains ethylene unsaturated acid. By this treatment, a partially crosslinked polymer containing 10% or more each surfactant and resin monomer is formed. Ultraviolet rays irradiate the polymer attached on the porous body to chemically bond the polymer and olefin.

Data supplied from the **esp@cenet** database - 12